



Millenia™ 20

Design	2-way acoustic suspension center, 5-driver, MagneShield™††
Crossover	2nd-order electro-acoustic at 2.0 kHz
High-Frequency Driver	25-mm (1 in) S-PAL™ dome, die-cast heatsink chassis, ferro-fluid cooled
Bass / Midrange Driver(s)	Two 115-mm (4-1/2 in) MLP™ cones, HTD™ system die-cast heatsink chassis, 25-mm (1 in) dual-layer voice coils
Midrange Driver(s)	-
Bass Driver	Two 115-mm (4-1/2 in) mineral-filled polypropylene cones, HTD™ system die-cast heatsink chassis, 38-mm (1-1/2 in) dual-layer voice coils
Low Frequency Extension	77 Hz (DIN)
Frequency Response:	
On-Axis	±2 dB from 110 Hz - 20 kHz
30° Off-Axis	±2 dB from 110 Hz - 18 kHz
Sensitivity - Room / Anechoic	92 dB / 89 dB
Suitable Amplifier Power Range	15 - 150 watts
Maximum Input Power	110 watts
Internal Volume	4.5 L / 0.16 cu ft
Impedance	compatible with 8 ohms
Weight	5.7 kg / 12.6 lb each
Height, Width, Depth	65.8 cm x 13 cm x 11.7 cm
	26 in x 5-1/8 in x 4-1/2 in
Finishes	Polished Aluminum, Black Chrome