



ART EMBRACING SCIENCE™



### Millenia™ 200

|                                |  |
|--------------------------------|--|
| Design                         | 2-1/2-way bass reflex, 6-driver, floorstanding design, MagneShield™††  |
| Crossover                      | 2nd-order electro-acoustic at 2.0 kHz, 2nd-order electro-acoustic at 800 Hz (bass drivers)   |
| High-Frequency Driver          | 25-mm (1 in) S-PAL™ dome, die-cast chassis, ferro-fluid cooled   |
| Bass / Midrange Driver(s)      | Two 115-mm (4-1/2 in) MLP™ cones, 25-mm (1 in) dual-layer voice coils, HTD™ system die-cast heatsink chassis                           |
| Midrange Driver(s)             | -  |
| Bass Driver                    | Three 115-mm (4-1/2 in) mineral-filled polypropylene cones, HTD™ system die-cast heatsink chassis, 25-mm (1 in) dual-layer voice coils |
| Low Frequency Extension        | 55 Hz (DIN)  |
| Frequency Response:            |  |
| On-Axis                        | ±2 dB from 87 Hz - 20 kHz  |
| 30° Off-Axis                   | ±2 dB from 87 Hz - 18 kHz  |
| Sensitivity - Room / Anechoic  | 92 dB / 89 dB  |
| Suitable Amplifier Power Range | 15 - 150 watts   |
| Maximum Input Power            | 130 watts  |
| Internal Volume                | 10.7 L / 0.38 cu ft  |
| Impedance                      | Compatible with 8 ohms   |
| Weight                         | 11.6 kg / 25.6 lb each   |
| Height, Width, Depth           | 120 cm x 13 cm x 15 cm   |
|                                | 47-1/4 in x 5-1/8 in x 6 in  |
| Finishes                       | Polished Aluminum, Black Chrome  |