



Millenia™ 30

Design	2-way acoustic suspension center, 5-driver, MagneShield™††
Crossover	2nd-order electro-acoustic at 2.0 kHz
High-Frequency Driver	25-mm (1 in) S-PAL™ dome, die-cast heatsink chassis, ferro-fluid cooled
Bass / Midrange Driver(s)	Two 140-mm (5-1/2 in) MLP™ cones, 25-mm (1 in) dual-layer voice coils, HTD™ system die-cast heatsink chassis
Midrange Driver(s)	-
Bass Driver	Two 140-mm (5-1/2 in) mineral-filled polypropylene cones, HTD™ system die-cast heatsink chassis, 25-mm (1 in) dual-layer voice coils
Low Frequency Extension	76 Hz (DIN)
Frequency Response:	
On-Axis	±2 dB from 110 Hz - 20 kHz
30° Off-Axis	±2 dB from 110 Hz - 18 kHz
Sensitivity - Room / Anechoic	94 dB / 91 dB
Suitable Amplifier Power Range	15 - 200 watts
Maximum Input Power	130 watts
Internal Volume	9.5 L / 0.33 cu ft
Impedance	Compatible with 8 ohms
Weight	8.0 kg / 17.6 lb each
Height, Width, Depth	90 cm x 15.1 cm x 13.7 cm
	35-1/2 in x 6 in x 5-1/2 in
Finishes	Polished Aluminum, Black Chrome