

ART EMBRACING SCIENCE"



Design	2-1/2-way bass reflex, 6-driver, floorstanding design, MagneShield [™] ††
Crossover	2nd-order electro-acoustic at 2.0 kHz, 2nd-order electro-acoustic at 1.0 kHz (bass drivers)
High-Frequency Driver	25-mm (1 in) S-PAL [™] dome, die-cast chassis, ferro-fluid cooled
Bass / Midrange Driver(s)	Two 140-mm (5-1/2 in) MLP™ cones, 25-mm (1 in) dual-layer voice coils, HTD™ system die-cast heatsink chassis
Midrange Driver(s)	-
Bass Driver	Three 140-mm (5-1/2 in) mineral-filled polypropylene cones, HTD™ system die-cast heatsink chassis, 38-mm (1-1/2 in) dual-layer voice coils
Low Frequency Extension	54 Hz (DIN)
Frequency Response:	
On-Axis	±2 dB from 87 Hz - 20 kHz
30° Off-Axis	±2 dB from 87 Hz - 18 kHz
Sensitivity - Room / Anechoic	94 dB / 91 dB
Suitable Amplifier Power Range	15 - 200 watts
Maximum Input Power	150 watts
Internal Volume	16.8 L / 0.59 cu ft
Impedance	Compatible with 8 ohms
Weight	12.9 kg / 28.5 lb each
Height, Width, Depth	133.3 cm x 15.1 cm x 17.5 cm
	52-1/2 in x 6 in x 7 in
Finishes	Polished Aluminum, Black Chrome